

SaltDogg — Mean On Ice, Man's Best Friend.

SaltDogg has the cost-effective, quality spreader you need with everything from manual walk-behind spreaders to insert salt spreaders and tailgate spreaders to cover as much winter ground as possible.



TAILGATE

Gravity or Auger Feed

TAILGATE SPREADERS

The most cost-effective high quality tailgate spreaders in the industry.



ELECTRIC DRIVE POLY HOPPER

Auger Feed

WHICH ELECTRIC DRIVE HOPPER SPREADER WORKS FOR YOU?

Available in Poly or Stainless Steel.

- 3/4 Yard
- 2 Yard Poly
- 2.2 Yard - 6 Yard Poly
- 1.5 Yard - 2 Yard Stainless Steel



ELECTRIC DRIVE STAINLESS HOPPER

Auger Feed

ELECTRIC DRIVE STAINLESS STEEL HOPPER SPREADERS

- 1.5 Yard - 2 Yard Stainless Steel
Spreading Material: Bulk Salt; 50/50 Salt/Sand mix



GAS HOPPER SPREADERS

V-Box Slide-In

GAS HOPPER SPREADERS

Available in stainless steel, powder coated carbon steel or rotationally molded polymer, these slide-in hopper spreaders are powered by a 10.5 HP gas engine.



2.5 - 3.0 CU YD MID-SIZE

304 stainless steel hopper

2.5 – 3.0 CUBIC YARD MID-SIZE

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 14-1/2" wide conveyor chain with 1/4" crossbars

Power Source: gasoline, electric, or hydraulic

- Capacity: 2.5 cu. yds. (8'), 2.75 cu. yds. (9'), 3.0 cu. yds. (10'),)
- 304 stainless steel hopper
- Adjustable Feedgate
- Available with 10-1/2 HP gas engine, 2 independent electric motors, or 2 independent hydraulic motors
- 14-1/2" wide conveyor chain with 1/4" crossbars
- Spinner chute has two adjustable internal baffles
- 4 Hinged top screens, 1/4" bars
- Inverted V
- Bolt-on spinner housing
- 14" Spinner disc



3.5 - 4.5 CU YD MUNICIPAL

304 stainless steel hopper

3.5 – 4.5 CUBIC YARD

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 14-1/2" wide conveyor chain with 1/4" crossbars

Power Source: gasoline or hydraulic

- Capacity: 3.5 cu. yds. (8'), 4.0 cu. yds. (9'), 4.5 cu. yds. (10')
- 304 stainless steel hopper
- Adjustable Feedgate
- Available with 10-1/2 HP gas engine or 2 independent hydraulic motors
- 14-1/2" wide conveyor chain with 1/4" crossbars
- Spinner chute has two adjustable internal baffles
- 4 Hinged top screens, 1/4" bars
- Inverted V
- Bolt-on spinner housing
- 18" Spinner disc



7 - 10 CU YD MUNICIPAL
Auger Driven

7 – 10 CUBIC YARD AUGER DRIVE

Spread Material: bulk salt, salt & sand mix

Feed Mechanism: 7" diameter, variable-pitch hard faced auger

Power Source: hydraulic

- Capacity: 7.0 cu. yds. (10'), 8.0 cu. yds. (11'), 9.0 cu. yds. (12'), 10.0 cu. yds. (14')
- 304 Stainless Steel Hopper
- Material spread up to 45'
- Two independent, direct-drive hydraulic motors
- 7" diameter auger with multi-pitch design
- Adjustable height spinner chute
- 3/8" heavy-duty hinged top screens with 4" peak
- 18" poly spinner disc

1471056SSH

MUNICIPAL HYDRAULIC DRIVE



6 - 8 CU YD MUNICIPAL

Conveyor Drive

6 – 8 CUBIC YARD

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 24" wide conveyor with 3/8" bars

Power Source: hydraulic

- Capacity: 6 cu. yds. (9'); 7, 8, 9 cu. yds. (10'); 10, 11, 13 cu. yds. (12'); 12, 13, 14 cu. yds. (14')
- 304 stainless steel hopper
- Material spread up to 40'
- Adjustable feedgate
- 24" wide conveyor with 3/8" bars
- Two independent direct drive hydraulic motors
- Choice of three gear box ratios: 50:1, 25:1 or 6:1
- Hinged top screens, 3/8" bars on 3" centers
- Inverted V, adjustable
- 2" drive shaft and bearings with 8-tooth sprockets
- 1-1/2" spring loaded idler shaft and bearings with 8-tooth sprockets
- Quick release hinged chute (no tools needed)
- 20" Poly spinner disc



9 - 11 CU YD MUNICIPAL

Conveyor Drive

9 – 11 CUBIC YARD

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 24" wide conveyor with 3/8" bars

Power Source: hydraulic

- Capacity: 6 cu. yds. (9'); 7, 8, 9 cu. yds. (10'); 10, 11, 13 cu. yds. (12'); 12, 13, 14 cu. yds. (14')
- 304 stainless steel hopper
- Material spread up to 40'
- Adjustable feedgate
- 24" wide conveyor with 3/8" bars
- Two independent direct drive hydraulic motors
- Choice of three gear box ratios: 50:1, 25:1 or 6:1
- Hinged top screens, 3/8" bars on 3" centers
- Inverted V, adjustable
- 2" drive shaft and bearings with 8-tooth sprockets
- 1-1/2" spring loaded idler shaft and bearings with 8-tooth sprockets
- Quick release hinged chute (no tools needed)
- 20" Poly spinner disc



12 - 13 CU YD MUNICIPAL

Conveyor Drive

12-13 CUBIC YARD

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 24" wide conveyor with 3/8" bars

Power Source: hydraulic

- Capacity: 6 cu. yds. (9'); 7, 8, 9 cu. yds. (10'); 10, 11, 13 cu. yds. (12'); 12, 13, 14 cu. yds. (14')
- 304 stainless steel hopper
- Material spread up to 40'
- Adjustable feedgate
- 24" wide conveyor with 3/8" bars
- Two independent direct drive hydraulic motors
- Choice of three gear box ratios: 50:1, 25:1 or 6:1
- Hinged top screens, 3/8" bars on 3" centers
- Inverted V, adjustable
- 2" drive shaft and bearings with 8-tooth sprockets
- 1-1/2" spring loaded idler shaft and bearings with 8-tooth sprockets
- Quick release hinged chute (no tools needed)
- 20" Poly spinner disc



14 CU YD MUNICIPAL

Conveyor Drive

14 CUBIC YARD

Spread Material: bulk salt, bulk sand, salt & sand mix

Feed Mechanism: 24" wide conveyor with 3/8" bars

Power Source: hydraulic

- Capacity: 6 cu. yds. (9'); 7, 8, 9 cu. yds. (10'); 10, 11, 13 cu. yds. (12'); 12, 13, 14 cu. yds. (14')
- 304 stainless steel hopper
- Material spread up to 40'
- Adjustable feedgate
- 24" wide conveyor with 3/8" bars
- Two independent direct drive hydraulic motors
- Choice of three gear box ratios: 50:1, 25:1 or 6:1
- Hinged top screens, 3/8" bars on 3" centers
- Inverted V, adjustable
- 2" drive shaft and bearings with 8-tooth sprockets
- 1-1/2" spring loaded idler shaft and bearings with 8-tooth sprockets
- Quick release hinged chute (no tools needed)
- 20" Poly spinner disc



LIQUID SPRAY SYSTEMS

Hydraulic Drive

FEATURES

- 12 VDC, 3 GPM/45 PSI electric diaphragm pump
- Hydraulic Drive: 4.5 GPM @ 1,750 RPM (150 PSI) with Proportioning Valve, Bronze pump, bronze gears, stainless steel shaft
- 30-gallon polymer reservoir (48"L x 13"W x 14"T)
- 55-gallon polymer reservoir (34"L x 23"W x 26"T)
- 105-gallon polymer reservoir (69"L x 20"W x 25"T)
- 200-gallon polymer reservoir (151"L x 28"W x 33"T)
- Low Pressure – empty tank light/buzzer indicator
- In-cab variable speed pump control (electric models)
- Adjustable Hydraulic proportioning valve (hydraulic models)
- Systems include tank, pump, cab controller, hoses, fittings, ball valve, filter, wiring, connectors, stainless steel brackets and tie-downs
- Enclosed pump system for corrosion resistance
- 304 stainless steel mounts



IN-BED LIQUID SPRAY SYSTEMS

For 6' & 8' Truck Beds

FEATURES

- 2" hitch mounted liquid spray system
- 335 gallon poly reservoir/bladder for 6' (#6196335) or 8' (#6198335) pick-up bed/flat bed with built-in tie points
- 7 gallons per minute diaphragm pump dispenses up to 50 gallons per lane mile.
- 12 VDC, 28 amps max, rear quick connect harness
- In-cab on/off control, standard. Pressure switch activates pump on demand
- Quick Detach PVC spray bar
- Stainless steel pump cover w/ LED license plate light
- Light weight, reinforced polymer reservoir rolls-up for bulkhead storage.
- Optional: 3/8"x50' hose reel with adjustable hand-held spray nozzle for side walks, bus shelters and hard to reach areas.
- Quick and simple, one-person installation with hitch pin.
- Lightweight and better visibility than fixed tank systems



UNDER TAILGATE - ELECTRIC

96" wide Dump Bodies

ELECTRIC MODELS

96" wide Dump Bodies

(for trucks without central hydraulics)

Spread Material: bulk salt, salt & sand mix

Feed Mechanism: 6" Auger with 3/8" flighting

Power Source: electric

- 304 stainless steel
- Material spread up to 25'
- Two 12 VDC direct drive motors (3/4 HP for auger, 1/2 HP for spinner)
- Standard discharge or center discharge
- 14" poly spinner and stainless steel dump body mounting plates
- 10-gauge trough has 3-point hinged bottom cover for easy access to entire auger assembly and one-person cleanout.
- 6" auger with 3/8" flighting, includes auger screen
- Sealed, self-aligning 1-1/4" diameter bearings with grease fittings
- Optional stainless steel spill shields



UNDER TAILGATE - HYDRAULIC

96" Wide Dump Bodies

HYDRAULIC MODELS

96" wide Dump Bodies

Spread Material: bulk salt, salt & sand mix

Feed Mechanism: 6" Auger with 3/8" flighting

Power Source: hydraulic

- Stainless steel or orange powder-coated carbon steel
- Material spread up to 40'
- Hydraulic power drives auger and spinner
- Standard discharge or left discharge
- 10-gauge trough has 3-point hinged bottom cover for easy access to entire auger assembly and one-person cleanout.
- 6" auger with 3/8" flighting, includes auger screen
- 18" poly spinner
- Sealed, self-aligning 1-1/4" diameter bearing with grease fitting
- Low-speed, high-torque orbital motors.
- Hydraulic safety lockout system.
- Optional powder coated spill shields
- Optional stainless steel spill shields



REPLACEMENT TAILGATE

Electric Dual Flight Auger

FOR DUMP BODIES AND DUMP INSERTS

Spread Material: bulk salt, salt & sand mix

Feed Mechanism: dual flight auger and breaker bar with mixing tines

Power Source: electric

- 304 stainless steel body
- Material spread up to 25'
- Two 12 VDC direct drive motors (3/4 HP for auger, 1/2 HP for spinner)
- Auger (5" O.D. x 2.4" I.D. x 20"L) with mixing tines
- Hinged 14" poly spinner



WALK-BEHIND

PROFESSIONAL GRADE FEATURES

- Large 1.5 - 2.5 cu.ft. poly hopper
- Carbon steel or stainless steel framework.

