



All lengths have a standard overall height of 50" and an inside width of 78". Standard conveyor door opening is 10" x 20". All major V-Box spreader components (unless stainless) are zinc primed and powder coated for a finish that is 700% more corrosive resistant than traditional paint and primer.

STANDARD SPECIFICATIONS

- 10 Gauge Construction (whether steel or stainless steel)
 - 2" Conveyor Drive Shaft
 - 25:1 Enclosed Lubricated Worm Gear (USA made)
 - Greasable Flange Bearings on Drive and Idler Shaft
 - 1/4" x 1-1/2" Chain Bar Flights
 - Adjustable Jack for Feed Gate (ground controlled)
 - 4 Tie Down Brackets
 - External Side Bracing
- Bolt In Conveyor Floor
 - Replaceable Chain Covers
 - 8 Tooth Keyed Drive Sprocket (replaceable)
 - 1-1/2" Idler Shaft
 - 24" wide, 2-1/4" Pitch Conveyor Chain
 - 10" x 20" Feed Gate Opening
 - Tilt Up Spinner Chute
 - 18" Urethane Spinner Disc
 - Straight Rear Wall and 26° Tapered Front Wall



FEATURES & OPTIONS

- Direct drive operation reduces number of moving parts, assuring dependable service.
- Under tailgate mounting allows normal use of dump body without interference from spreader.
- Rugged 7-gauge trough has 3-point hinged bottom cover that provides easy access to entire auger assembly for easy, one-person cleanout.
- Spreads from 4' to 40' of rock salt, free-flowing granular materials or chemicals.
- Auger is supported by 1-1/4" steel shaft ends and has right and left flighting to the discharge port delivering a continuous, consistent flow of spreading material.