

STANDARD EM SERIES ADVANTAGES INCLUDE:

New wider and deeper platform sizes

Steel Platforms: Aluminum Platforms:

- 40" x 84" + 4" ramp - 44" x 84" wedge

- 46" x 84" + 4" ramp - 50" x 84" wedge


44" x 84" wedge50" x 84" wedge

- Bed extension with reinforced angle along entire width makes installation easier and reduces dishing
- 36" to 56" bed height range (Note: Larger platform 46"+ 4" & 50" wedge fits 39" (laden) 56" bed height only)
- Grease fittings and maintenance free bearings at all major hinge points
- Easier installation with preset "A" dimension. Pump and cylinder installed and tested at factory
- Roll pins replaced with bolts to allow easier maintenance
- Underride option available
- Single / Dual (2,500 lb. 3,300lb.) cylinder models available with all the above features
- Snubber kit reduces potential liftgate wear caused by vibration during travel
- Powder coat finish with zinc primer on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion


OPTIONAL EQUIPMENT:

 Hand-Held Pendant Control allows driver to operate the truck from the ground or bed level





EMW-25, EMW-33 FULL DIP (WEDGE PLATFORM)





EM Series Gate in stowed position



FLIPWAY GATE



Bolt-on parking bar shown above.



Optional Steel Dock Bumper w/Step and Rubber Pad.

Order your Liftgate today, and We'll ship it Tomorrow.



The EM is one of many liftgates in our Quick-Lift Program – Waltco will ship up to three EM liftgates by the end of the following business day. Or we pay the freight.

www.waltcoliftgates.com/quicklift

Products shown may feature optional equipment Content subject to change without notice.

SPECIFICATIONS

MODEL	CAPACITY	PLATFORM	RAMP
EM-25*	2,500 lbs.	40"x 84"	4"
EMW-25	2,500 lbs.	44"x 84"	Wedge
EM-25	2,500 lbs.	46"x 84"	4"
EMW-25*	2,500 lbs.	50"x 84"	Wedge
EM-33	3,300 lbs.	40"x 84"	4"
EMW-33	3,300 lbs.	44"x 84"	Wedge
EM-33	3,300 lbs.	46"x 84"	4"
EMW-33	3,300 lbs.	50"x 84"	Wedge
EM-33TC	3,300 lbs.		
AP (Aluminum Platform)			
EMW/AP-25	2,500 lbs.	44" x 84"	Wedge
EMW/AP-25	2,500 lbs.	50" x 84"	Wedge
EMW/AP-33	3,300 lbs.	44" x 84"	Wedge

50" x 84"

Note: "EMW" denotes full-dip wedge style platform models

EMW/AP-33

The 46"+4" platform and the 50" wedge have a minimum bed height of 39" laden

*Eligible for Waltco's Quick-Lift
Program (see details below).

Bed Ht: 36"-56"

OPTIONAL EQUIPMENT (CONTINUED):

3.300 lbs.

- Remote Pump Mounting Kit offers the flexibility to install the pump unit independently from the liftgate mount assembly when mounting space is an issue (recommended for low-bed height mounting applications)
- Walk Ramp Installation Kit allows liftgate to be used in conjunction with slide out walk ramp (for bed heights 42" 54" only)
- Power-Down Operation for consistent performance regardless of weather conditions or temperature (dual solenoid)
- Cab Shut-Off Switch allows operator to shut off power to control switches, preventing unauthorized use of the liftgate
- Dual Controls (street-side control) for added driver convenience
- Two step Steel Dock Bumpers with bolt on capability protect the liftgate from damage caused by backing into loading docks
- Receiver-style hitch (Class IV 10,000 lb. rating with 1,000 lb. tongue weight) adds trailer towing versatility to vehicles with E Series liftgates (Draw bar and ball hitch not included; minimum 47" Bed Height on single cylinder; 39" to 56" Bed Height with twin cylinder)
- Draw Bar Kit (Class III) gives 13" ball height range flexibility (Ball hitch not included)
- Optional dual cart stops (only available on wedge ramps)
- Customized Options contact factory

WALTCO

T: **800.211.3074**F: 800.211.3075
Email: sales@waltco.com
Web: www.waltcoliftgates.com

Waltco Lift Corp. Corporate Office United States

285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418

Waltco Lift Corp. United States

620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149

Waltco Lift Inc. Canada

90 North Queen St. Etobicoke, ON M8Z 2C5 P: 888.343.4550