


## STANDARD WDVBG SERIES ADVANTAGES INCLUDE:

- Lifetime warranty UHMW slide pads
- Fold-down rear retention rails
- Power down
- Hydraulic power open and close
- Mechanical lock
- Power unit preinstalled and tested in combination pump/battery box with pre-mounted hanger brackets
- Standard steel platforms
- Series Hydraulic Circuit Design and Automatic Self-Leveling System
  - Load can be offset without compromising capacity
  - Platform always lifts parallel to truck bed, even on uneven road surfaces
  - Fully lubricated cylinders reduce seal wear and closed hydraulic system keeps out fluid contaminates
- Pre-mounted marine potted toggle switches with half rubber boot
- LED lights
- Thermally protected motors
- Bottom stops for dock loading



Revolutionary Series Hydraulic Circuit Design



WDVBG Series Gate in stowed position offers simplicity and reduced maintenance



# **NDVBG**

## BOTTLED GAS GATE



### 1/2" Thick Heavy Duty Independent Bumper:

Bumper that protects both the dock and the liftgate. Bumper pad is fixed while the trailer moves during dock loading. This prevents rubbing damage against dock. Bumper is independent of column. It takes the impact without damage to the column.



# **UHMW Slide Pads:**

Lifetime warranty eliminates the cost of replacing rollers and downtime.



## **Pre-Mounted Marine Potted** Toggle Switch:

Protected against elements, pre installed in a location that allows easy viewing of the platform work

# **Hands Free Positive Latching System:**

Mechanical design holds the platform secure and eliminates problems that occur with hydraulic/electric systems.

#### **SPECIFICATIONS**

MODEL	CAPACITY	PLATFORM	FOLDING RAMP
WDVBG-35	3,500 lbs.	36" x 80"	16" x 45"
WDVBG-35	3,500 lbs.	42" x 80"	16" x 45"
WDVBG-45	4,500 lbs.	36" x 80"	16" x 45"
WDVBG-45	4,500 lbs.	42" x 80"	16" x 45"

Note: Platform increases to 86" with purchase of 102" wide vehicle option

# **OPTIONAL EQUIPMENT:**

- Dual controls adds a street side raise/lower control for driver convenience
- Hand-held pendant control allows driver to operate the liftgate from ground or bed level
- Gravity down on demand
- Cab mounted power shut-off switch allows operator to shut-off power to liftgate control switch(s) to prevent unauthorized use of the liftgate
- Platform materials:
  - Aluminum with galvanized steel rails
  - Aluminum with aluminum rails
  - Galvanized steel
  - Bar grating
- Galvanized main frame
- Dual pump and motors
- Auxiliary hand-held backup switch
- Batteries (Dual purpose, AGM, Deep cycle)
- Customized options contact factory



T: 800.211.3074 F: 800.211.3075 Email: sales@waltco.com Web: www.waltcoliftgates.com Waltco Lift Corp. **Corporate Office United States** 

285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418

Waltco Lift Corp. **United States** 

620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149

Waltco Lift Inc. Canada 90 North Queen St. Etobicoke, ON M8Z 2C5