

STANDARD WZ SERIES ADVANTAGES INCLUDE:

- Slider design is compatible with both roll-up and swing-type doors. The advantages of swing-type doors include maximum use of interior cargo space and maximum door opening capability for easy loading and unloading.
- Dual-lift and dual-tilt cylinder design allows for more positive platform control, greater load stability, and enhanced speed and reliability even in cold temperatures
- Cylinder tilt feature allows the operator to level the platform no matter what the terrain
- Torsion-assisted platform is lightweight, corrosion-resistant, and easy to fold and unfold
- Chain Driven slide system powered by a hydraulic motor provides smooth, even movement of the platform into and out of its transit position
- Power Up / gravity down / power tilt hydraulic system
- Electric cylinder locks prevent the platform and cargo from lowering in the event of a hydraulic line failure
- Platform marker lights provide increased visibility and safety while the liftgate platform is in the open working position
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

A large tilting platform that adjusts for varying grades, puts your cargo on level ground.



WZ Series Gate in stowed position

Products shown may feature optional equipment. Content subject to change without notice.





SLIDE-AWAY GATE









Platform from stored to raised position

T: 800.211.3074

Email: sales@waltco.com Web: www.waltcoliftgates.com

F: 800.211.3075

SPECIFICATIONS

MODEL	CAPACITY	PLATFORM	PLATFORM CONSTRUCTION	RAMP
WZ-44	4,400 lbs.	71" x 96"	Aluminum	Wedge
WZ-44	4,400 lbs.	79″ x 96″	Steel/Aluminum	Wedge
WZ-55	5,500 lbs.	71″ x 96″	Steel/Aluminum	Wedge
WZ-55	5,500 lbs.	79″ x 96″	Steel/Aluminum	Wedge

Note: Minimum of 85" clearance/overhang required

OTHER STANDARD FEATURES:

- Thermally protected power unit shuts down the power to the liftgate before heat build-up or low voltage due to a bad ground can cause permanent damage to electrical components. This feature minimizes costly downtime and repairs
- Steel/aluminum or all steel platform for superior strength and durability
- Stationary push-button control box lets the driver operate the liftgate in full view of the rear of the vehicle, platform and cargo
- Hand-held remote control lets the driver operate the liftgate from the ground, platform or bed level
- Weather-resistant power unit enclosure protects vital liftgate components from corrosion and other weather-related damage

OPTIONAL EQUIPMENT:

- Cab Shut-Off Switch allows operator to shut off power to control switches, preventing unauthorized use of the liftgate
- Auto-tilt feature tilts the platform down at ground level when lowering the gate, then returns the platform to level position before raising
- Split cart stops keep one or two rolling carts secure on the platform while the platform is being lowered, raised or leveled. The split allows the operator to move a single cart off the platform, while the second remains retained
- Customized Options contact factory

Waltco Lift Corp. Corporate Office United States 285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418 Waltco Lift Corp. United States 620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149 Waltco Lift Inc. Canada 90 North Queen St. Etobicoke, ON M8Z 2C5

© Copyright 2013 WALTCO 2.13

Bed Ht: 44"- 53"